



Ph: 800-277-3207 Fax: 888-845-9491  
E-mail: [info@tamarrontechnology.com](mailto:info@tamarrontechnology.com)  
[www.tamarrontechnology.com](http://www.tamarrontechnology.com)  
Cincinnati, Ohio

## Tam Tech Concrete Removal

(Prevents Concrete Build-Up)

### Product Description:

Tam Tech Concrete Removal will prevent concrete from bonding to mixers, molds, pump trucks, ready-mix trucks, buckets, hoppers, screeds, etc. It is a great labor saver ! It makes it easier to remove concrete build-up from most metal surfaces including the inside of concrete mixers.

### Features & Benefits:

- Prevents concrete build-up
- Works in hot weather
- Easy removal of concrete, reduces labor costs
- Works on concrete mixers and pump trucks
- Ideal for precast plants and block plants

### Instructions:

First remove the concrete from the surfaces to be coated. High pressure cold water can be used for removal. Let dry. Apply at 400 square feet per gallon. Use a light spray or brush. Re-apply at end of each shift. Tools and hardware may be soaked in product for a couple of days for easy removal of concrete. If customer prefers a thinner product, it can be diluted with mineral spirits, xylene or diesel fuel.

### Packaging:

5 gallon (18.9 L) pails and 55 gallon (208 L) drums

### Coverage:

400 sq ft/ gallon (9.8 sq m/ liter)

#### Warranty:

Tamarron Technology warrants for 12 months from the date of manufacture that the product is free of manufacturing defects and conforms to the company's published technical data and specifications. Tamarron Technology shall only be liable under this warranty if the product has been applied, used and stored in accordance with the instructions on this technical data sheet. Disclaimer: Neither manufacturer nor seller has any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. Neither manufacturer or seller assume any liability for personal injury, loss or damage resulting from the use of the product. In the event that the product shall prove defective, buyer's exclusive remedy shall be as follows: Seller or manufacturer shall, upon request of buyer, replace any quantity of the product which is proved to be defective or shall, at its option, refund the purchase price of the product upon return of the product.



**Limitations:**

Surfaces will be slippery after application. Do not use as a form release agent.

**Shelf Life:**

Two years in unopened containers.

**Warning:**

**Product is combustible.** Skin contact may cause irritation. Remove clothing if contaminated and wash skin thoroughly with soap and water. If eye contact occurs, flush with water and contact physician.

Avoid prolonged breathing of vapors and prolonged skin contact. Use safety glasses and wear rubber gloves. Use with adequate ventilation or if ventilation is poor, refer to MSDS for further information. Do not use near heat or flame. Do not cut the top off of drum. See MSDS for complete information. For industrial use only. Keep out of reach of children.