



Ph: 800-277-3207 Fax: 888-845-9491
E-mail: info@tamarrontechnology.com
www.tamarrontechnology.com
Cincinnati, Ohio

TAMTECHseal Wet Look WB **(Waterbased Wet Look Sealer)**

Product Description:

TAMTECHseal Wet Look is designed to provide a gloss look for concrete, pavers and other masonry applications. It will seal and protect the surfaces of concrete & pavers while enhancing the beauty. TAMTECHseal Wet Look can also stabilize/harden the sand in the joints. This polymer is UV stable and forms a tremendous bond to the substrate. The product also resists weather, water intrusion, freeze thaw damage and staining. The sealer is breathable, thus moisture is not trapped in the substrate. It is an interior or exterior product that can be used on new or existing concrete applications.

Features & Benefits:

- Seals & protects concrete
- Wet / Gloss look
- Waterbased, safe to use, VOC compliant
- Resists water, surface staining
- Sealed areas easier to keep clean
- Reduces concrete dusting
- Breathable

Technical Data:

Form: white liquid

pH: 8.2

Specific Gravity: 1.02

Weight/gallon: 8 lbs

Freezing Point: 35 degrees F

Cured Coating: Resists temperatures as high as 160 degrees F

Resists temperatures as low as minus 50 degrees F

Warranty:

Tamarron Technology warrants for 12 months from the date of manufacture that the product is free of manufacturing defects and conforms to the company's published technical data and specifications. Tamarron Technology shall only be liable under this warranty if the product has been applied, used and stored in accordance with the instructions on this technical data sheet. Disclaimer: Neither manufacturer nor seller has any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. Neither manufacturer or seller assume any liability for personal injury, loss or damage resulting from the use of the product. In the event that the product shall prove defective, buyer's exclusive remedy shall be as follows: Seller or manufacturer shall, upon request of buyer, replace any quantity of the product which is proved to be defective or shall, at its option, refund the purchase price of the product upon return of the product.



Instructions:

Surface must be clean and dry. Remove all dust, dirt, paint, efflorescence, oil and loose debris. A leaf blower is recommended to remove the dust and debris. For paver applications, be sure sand is filled in joints to the required level slightly below the top of the pavers. Completely remove all remaining sand. Apply product uniformly with a pump-up sprayer, roller or use low pressure spray equipment, about 10 psi. Use a fan type spray nozzle and apply a coat to saturate the surface and avoid puddles. For a more uniform application, cross roll. Let dry. On vertical surfaces, start from the top and apply the sealer uniformly and work down. Brush out run-downs. If necessary on more porous or older surfaces, apply additional coats to achieve desired finish. Do not leave excess or pooled material on the surface. Product will dry to the touch in typically 45-60 minutes at 74 degrees F. Keep water and traffic off for 24 hours. Cooler temperatures will slow down cure time. Clean equipment with water before it cures.

Packaging: One gallon units (six/case), five gallon pails and 55 gallon drums

Coverage: Concrete: 200-300 sq ft /gal, Bricks: 100-200 sq ft /gal,
Retaining Walls: 150-300 sq ft/gal.
Coverage rate will depend on texture and porosity of the surface.

Limitations:

Do not apply product to a damp surface. Always do a small test to ensure desired look and performance of the sealer. The minimum application temperature is 45 degrees F for the previous 24 hours. In hot weather it is recommended that product be applied in the cooler morning hours.

Shelf Life:

Two years in unopened containers.

Warning:

Skin or eye contact may cause irritation. If eye contact occurs, flush with water for 15 minutes. For skin contact, wash with soap and water. Over application can cause surface to become slippery when wet.

Use safety glasses and wear gloves with protective clothing. Use with adequate ventilation. Do not swallow or inhale. See MSDS for complete information.

For Industrial Use Only. Keep Out Of Reach Of Children.