



Ph: 800-277-3207 Fax: 888-845-9491  
E-mail: [info@tamarrontechnology.com](mailto:info@tamarrontechnology.com)  
[www.tamarrontechnology.com](http://www.tamarrontechnology.com)  
Cincinnati, Ohio

## **Tam Tech Finishing Aid**

(Hot Weather Finishing Aid / Helps To Prevent Surface Cracking)

### **Product Description:**

Tam Tech Finishing Aid is a proprietary product designed to provide more time to finish concrete flatwork in hot, dry or windy conditions. It helps contractors produce high quality concrete flatwork and avoid concrete setting before they can complete the finishing operations. The product works by reducing the amount of moisture loss from the concrete during finishing. Thus it also helps to also prevent plastic shrinkage cracking on the surface. It is supplied in a concentrate and it is very economical at a dilution ratio of 10 to 1 with water.

### **Features & Benefits:**

- Prevents rapid drying of the concrete during hot weather
- Provides more finishing time in hot weather
- Helps prevent plastic shrinkage cracks on the surface
- Ideal for concrete finishing in hot, dry, windy conditions
- Reduces concrete crusting in hot weather
- Does not affect concrete strength
- Compatible with sealers

### **Instructions:**

Dilute Tam Tech Finishing Aid with ten gallons of water to one gallon of product and mix completely. Apply diluted product with a low pressure fine spray at 400 to 500 sq ft per gallon. (9.8 sq m/liter) Product should be sprayed in a fine mist after the screeding process or after bullfloating. When conditions are very dry or windy, reapply product between finishing operations. Clean up with soap and water.

### **Packaging:**

1 gallon (3.8 L) units, (6 per case), 5 gallon (18.9 L) pails and 55 gallon (208 L) drums

#### **Warranty:**

Tamarron Technology warrants for 12 months from the date of manufacture that the product is free of manufacturing defects and conforms to the company's published technical data and specifications. Tamarron Technology shall only be liable under this warranty if the product has been applied, used and stored in accordance with the instructions on this technical data sheet. Disclaimer: Neither manufacturer nor seller has any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. Neither manufacturer or seller assume any liability for personal injury, loss or damage resulting from the use of the product. In the event that the product shall prove defective, buyer's exclusive remedy shall be as follows: Seller or manufacturer shall, upon request of buyer, replace any quantity of the product which is proved to be defective or shall, at its option, refund the purchase price of the product upon return of the product.

**Coverage:**

400 to 500 sq ft / gallon (9.8 sq m/liter) after dilution with 10 gallons of water per 1 gallon of Tam Tech Finishing Aid. Thus each gallon of Tam Tech Finishing Aid will cover over 4400 sq ft. (372 sq m)

**Limitations:**

Do not use as a curing compound. Do not apply during final troweling operations. Product will not work after concrete cures. Do not allow the stored product to freeze. For colored concrete, apply product to a test area first. If product is spilled on fully cured concrete, clean immediately and rinse with water. Apply a curing compound after finishing operations.

**Shelf Life:**

One year in unopened containers. Do not allow stored product to freeze since it is water based.

**Warning:**

Skin or eye contact may cause irritation. If eye contact occurs, flush with water. Use safety glasses and wear gloves. See MSDS for complete information. For industrial use only. Keep out of reach of children.